

General Specifications

Wireless communication	Bluetooth v4.2 + BLE
Enclosure rating	IP54 / IK10*
Enclosure material	ABS / PC
Operating temperature	-5 °C to +45 °C
Storage temperature	-40 °C to +60 °C
Storage temperature	5% to 95% Non-condensing
Light beacon	RGB colour indicator
Power limit control	Mode 3 PWM control according to ISO/IEC 61851-1
Dimensions (D x W x H)	200 x 335 x 315 mm
Weight	4 kg
External input	Remote charging activation
Safety protection	Welded contactor detection



Optional devices

Protections	DC 6 mA leakage detection
Power limit control**	Home BeON sensor
Type 2 socket protection	Locking System
Type 2 charging socket	Shutter
Tethered cable	Type 1 straight + cable holder Type 2 straight + cable holder
Pedestal	
Customisation	Logo customisation

* IK08 in some components appended to the body, i.e., beacon light.

** Single-phase models only.

Models

Models	S	T
AC power supply	1P + N + PE	3P + N + PE
AC input voltage	230 V AC +/-10%	400 V AC +/- 10%
Maximum input current	32 A	32 A
Maximum input power	7,4 kW	22 kW
Number of plugs	1	1
Maximum output power per outlet	7,4 kW	22 kW
Maximum output current per outlet	32 A	32 A
AC output voltage	230 V AC (1P+N+PE)	400 V AC (3P+N+PE)
Socket Type	1 x Type 2 Socket 	1 x Type 2 Socket 

Home BeON Compatible

Intelligent sensor for single-phase systems

Home BeON is a sensor that can be easily added to a fuse box to dynamically adjust the current supplied to the EV to the power available at any given time, thus avoiding overloading.



Pedestal



1500 mm

Tótem PdV



1550 mm

Pedestal

Material:

Aluminio 5754

Peso:

10 kg

Dimensiones:

1500x373x150 mm

Tótem PdV

Material:

Poliestireno

(1,5 mm de ancho)

Peso:

4 kg

Dimensiones:

1500x373x150 mm